TRANSDUCER.

BACKGROUND OF THE INVENTION

5   1. Field of the invention

The present invention relates to a transducer or, in other
words, to an element for sound-reproduction and/or
recording, more particularly a loudspeaker or microphone.

10

2. Discussion of the Related Art

For simplicity's sake, in the description following
hereafter it will only be spoken about transducers for
15   reproducing sound, in other words, sound-reproducing
devices, however, such transducers relate to reproducing as
well as recording devices.

Still more particularly, the invention relates to
20   piezoelectric reproducers, of the type using a vibration
membrane which is composed of a carrier and a piezoceramic
disk attached upon this carrier.

In the Belgian patent No. 09700309, improvements to the
25   aforementioned type of transducers are described which
consist in that a wall is provided which is situated at a
small distance to the vibration membrane, such that an
attenuating effect on the sound vibrations generated by the
vibration membrane is obtained.

30

In the Belgian patent No. 09700934, also improvements to
the aforementioned type of transducers are described, which
substantially consist in that the vibration membrane is
provided with an attenuating layer which comprises metal

particles.

With the thus known piezoelectric reproducing elements, the
carrier of the membrane always consists of a metal disk.

5

SUMMARY OF THE INVENTION

Although the reproducing elements, as described in the
aforementioned patents, deliver very good results, the
applicant of the present patent has found out that, by
10   replacing the aforementioned metal membrane by a membrane
made of a sound-attenuating material, such as synthetic
material, a polymer or such, considerably better results
are obtained.

15   BRIEF DESCRIPTION OF THE DRAWINGS

With the intention of better showing the characteristics of
the invention, hereafter several embodiments of the element
according to the invention are described, with reference to
20   the accompanying drawings, wherein:

figure 1 represents the vibration modes in square metal
membranes;
figure 2 represents the vibration modes in rectangular
25   metal membranes;
figure 3 represents the vibration modes in circular metal
membranes;
figure 4 represents a diagram of the course of the
frequency reproduction of known piezo-reproducers with
30   metal membrane;
figure 5 represents the diagram of the course of the
frequency spectrum measurement of a sinus of 1kHz on an
electro-dynamic loudspeaker;
figure 6 represents a diagram similar to that of figure 5,

however, for a piezoceramic disk on a metal membrane;

figure 7 represents a schematic representation of a transducer according to the invention;

figure 8 represents the electric diagram of a piezo-disk under load;

figure 9 represents the electric diagram of a piezo-disk glued onto a plate of synthetic material;

figures 10 and 11 represent schematic embodiments of reproducing elements according to the invention;

figures 12 and 13 represent the function course of transducers according to figures 10 and 11;

figures 14 to 19 represent different forms of transducers;

figure 20 represents the diagram of the harmonic contents of 1kHz of a transducer according to the invention;

figure 21 represents the frequency characteristic of a transducer according to the invention;

figure 22 represents a cross-section of a suspension possibility of a transducer according to the invention;

figure 23, at a larger scale, represents the portion indicated by F23 in figure 22;

figure 24 represents a view according to arrow F24 in figure 23;

figures 25 and 26 represent electric diagrams of attenuations in the membrane of a transducer according to the invention;

figure 27 is a view similar to that of figure 23;

figure 28, at a larger scale, represents the part indicated by F28 in figure 27;

figure 29 represents a cross-section of a transducer according to the invention in combination with a front plate;

figure 30 represents a view according to arrow F30 in figure 29;

figure 31 represents the electric diagram of the frequency-

filtering function of the front plate according to figure 29;

figure 32 represents a transducer with a two-part ceramic disk;

5   figure 33 represents a cross-section of a particular embodiment of a transducer according to the invention;

figure 34, at a larger scale, represents the part indicated by F34 in figure 33;

figure 35 represents a top view of another possible form of

10   embodiment of a transducer according to the invention;

figure 36 represents a cross-section according to line XXXVI-XXXVI in figure 35;

figure 37 represents a diagram of the frequency characteristics of a transducer according to figure 35;

15   figure 38 represents a variant of figure 22;

figure 39 represents a diagram similar to that of figure 37, however, for a transducer with a cylindrical polymer membrane and a cylindrical ceramic disk;

figure 40 represents the frequency characteristic for a

20   transducer, as intended in figure 32;

figures 41 and 42 represent cross-sections of transducers according to the invention which are provided in a particular or an existing housing, for example, the housing of a cellular phone;

25   figure 43 represents a transducer according to the invention, formed by a cellular phone-housing which functions as a membrane, and a piezoceramic disk provided therein.

figure 44 represents another variant of a transducer

30   according to the invention.

DESCRIPTION OF PREFERRED EMBODIMENTS

In the aforementioned Belgian patent No. 09700309, it is

indicated that the combination of a piezoceramic disk with a metal membrane which is attached at its circumferential line by means of a flexible glue, may exert a strong influence upon the lowermost frequency of resonance.

Indeed, as is known, the frequency of resonance of a transducer which is composed of, for example, a piezoceramic disk which is glued onto a brass membrane, is determined by:

$$f_r = \frac{t}{S} \sqrt{\frac{y}{d(1 - r^2)}}$$

wherein:

t = thickness of the membrane
S = surface of the membrane
y = Young modulus
r = Poisson ratio.

When suspending such membrane at the edge, this formula becomes:

$$f_r = K \cdot \frac{t}{S} \sqrt{\frac{y}{d(1 - r^2)}}$$

wherein K is an assembly factor.

The edge width of the suspension and the viscosity of the glue are factors exerting an influence onto the frequency

of resonance.

The formula of the frequency of resonance then becomes:

$$f_r = \frac{b \cdot v \cdot t}{D_4 \cdot S} \sqrt{\frac{y}{d(1-r^2)} \cdot \frac{1}{G}}$$

wherein:

$\dfrac{1}{G} = 1$

b = width of supporting edge for glue

D_4 = diameter of the membrane which is not supported

V = viscosity of the glue.

The distance between the membrane and the surface of the front wall increases the apparent weight of the membrane.

The frequency of resonance then becomes:

$$f_r = \frac{b \cdot v \cdot t}{D_4 \cdot S} \sqrt{\frac{y}{d(S_1/D_1)(1-r^2)} \cdot \frac{1}{G}}$$

wherein:

$\dfrac{1}{G} = 1$

S_1 = surface of free-moving part

D_1 = distance between moving part of membrane and wall

Due to this suspension and construction, frequencies can be reproduced starting from 100Hz up to 20 kHz.

5

In order to attenuate the resonance peaks which occur in the metal membrane, in the Belgian patent No. 09700934 a solution was presented which consists in that a layer of flexible glue, such as, for example, silicones or

10 elastomers filled with metal powder, can be provided on the membrane, which can lower the frequency of resonance and, at the same time, attenuate the peaks of the frequency of resonance and move them to another frequency.

The patents mentioned in the aforegoing describe a

15 piezoceramic loudspeaker consisting of the composition of a piezoceramic disk, glued onto a metal membrane, for example, made of brass.

The drawbacks of this combination are that the frequency

20 reproduction is not flat and that a strong harmonic distortion is created which depends on the frequency contents, such that the reproduction quality for music and speech is insufficient.

25 In order to prevent these drawbacks, the present invention relates to a piezoelectric reproduction element, whereby the piezoceramic disk is glued onto a membrane which consists of a relatively flexible material, more particularly a material which attenuates sound vibrations,

30 for example, a synthetic material, still more particularly a polymer.

Preferably, the aforementioned disk is glued onto the

membrane by means of a hard glue, whereas the whole unit
can be glued at its circumferential edge into a suitable
frame, for example, made of synthetic material.

5   This construction has a flat frequency characteristic, the
quality of which is more than sufficient for reproducing
music as well as speech for industrial applications with a
low harmonic distortion of an average 3% between 100Hz and
20kHz.

10

The theoretical explanation following hereafter explains
this improvement.

The membrane made of metal has a natural resonance which
15   will fragment into different vibration zones according to
the vibration frequency which is supplied, to wit the so-
called vibration modes.

The vibration modes in a square, rectangular or circular
20   membrane, according to figures 1, 2 and 3, respectively,
are a multiple or harmonic of the base frequency.

When a piezoceramic disk is glued onto such membrane, new
vibration modes are created. Apart from the fundamental
25   frequency of resonance-sound pressure, the acoustic
reproduction of such construction further has a number of
resonances which depend on the vibration modes of the
transducer which is composed of a metal membrane and a
piezoceramic disk. The frequency reproduction of a piezo-
30   loudspeaker constructed with such transducer therefore
yields a selective frequency reproduction, such as
represented in figure 4.

In this figure, one will observe clearly stronger

reproductions at 300Hz, 1500Hz, 2500Hz, 3000Hz, 5600Hz,
7000Hz, 8500Hz, 9000Hz and 15kHz, whereby 300Hz is the
self-resonance of the whole system, thus, of the mounted
transducer in a housing. The other frequency peaks either
5   are harmonics of the system's frequency of resonance or the
sum of the harmonic with the vibration modes of the
transducer. The frequency minimums are the sum of the anti-
resonance points of the transducer and harmonics at those
frequency points.
10

When a frequency-spectrum measurement is performed of a
sinus of 1kHz on an electrodynamic loudspeaker, the
reproduction of the base wave on 1Khz and its higher
harmonics at 2kHz, 3kHz, 6kHz, 7kHz, as represented in
15   figure 5, are obtained.

When the same measurement is performed at a piezoceramic
disk which is provided on a metal membrane, a frequency
spectrum reproduction of the supplied base frequency of
20   1kHz is obtained, and higher harmonics of 2kHz, 3kHz, 4kHz,
5kHz, but moreover one obtains reproductions of lower
harmonics of 500Hz, 250Hz, and apart therefrom also
reproductions of complex resonance vibrations of modes
originating from the transducer, for example, 1300Hz,
25   1600Hz, 2500 Hz, 3500 Hz, such as becomes clear from figure
6.

A piezoceramic disk glued onto a metal membrane therefore
vibrates with a variable amplitude in function of the
30   frequency. A loudspeaker must reproduce all frequencies
with one and the same sound pressure. In order to obtain
this, the effect of the harmonics must be eliminated with
the vibration modes, which is realized by drastically
lowering the natural resonant frequency of the vibration

system, such that the higher harmonics have a much smaller
amplitude in the audible range.

The formula of the frequency of resonance is:

$$f_r = \frac{t}{S} \sqrt{\frac{y}{d(1 - r^2)}}$$

in which f_r can be lowered by using a material for the
membrane with a low modulus of y (Young).

Modulus of y in Mpa:
brass   62.000
nickel   200.000
nylon   2.700
elastomere   5.000

Ratio of Poisson:
brass   0,36
nylon   0,38
Density d in kg/m³ :
brass   8,5
nickel   8,9
nylon   0,9
elastomer   0,95

The part $\dfrac{y}{d(1 - r^2)}$ when using polymers becomes 3 to 4
times smaller. A frequency of resonance of 200Hz therefore
drops towards +/- 60 Hz.

As is known, no self-resonances can occur in plates when a
sufficient elastic resistance is present. In figure 7, a

transducer 1 according to the invention is represented
which consists of a piezoceramic disk 2, glued onto a plate
3 of synthetic material, for example, a polymer, in other
words, a transformer of alternating current to sound waves.
5   In this figure, the air vibrations are represented by 4.

The equivalent electric diagram of a piezo-disk under load
is represented in figure 8, in which the indicated elements
have the following signification.
10

$C0$ = capacitance of the loaded transducer
    $R0$ = the dielectric loss of the transducer
        $[2 \Pi (C0 + C1) \tan \delta]^{-1}$
$R1$ = mechanical loss in the transducer
15 $C1$ = rigidity of the piezo-material
$L1$ = the mass of the piezo-material.

Figure 9 represents an equivalent electric scheme of a
piezo-disk glued onto a polymer plate, whereby the
20 indicated elements, apart from those according to figure 8,
have the following signification.

$C2$ = rigidity of the polymer plate
$L2$ = mass of the polymer plate
25 $R2$ = mechanical losses in the glue layer and
        in the polymer plate.

Resonances can not occur when the circuit is not tuned to
the frequencies fulfilling the condition of resonance. The
30 parallel load of the polymer plate, whether in rigidity or
mass, and the solid attachment to the piezo-disk prevent
the condition of resonance.

C2 = y2 of polymer is 10^3 MPa

C1 = y1 of ceramics is 10^5 MPa.

In order to obtain a parallel resonance (Frp) condition,

Frp = L1 + L2 and CO must fulfill the following condition:

$$Frp = \frac{1}{\sqrt{2 \Pi (L1 + L2)\ CO}}$$

Frp is highly resistive.

In order to obtain a serial-resonance Frs condition,

Frs = L1 and C1 + C2 must fulfill the following condition:

$$Frs = \frac{1}{\sqrt{2 \Pi L1(C1 + C2)}}$$

Frs is low resistive.

The influence of the polymer plate is very high with resonance conditions:

-   R1 and R2 is the serial impedance which determines the quality of the circuit in resonance and which will prevent the occurrence of selective resonance conditions.

-   C1 and C2 is the rigidity of the system. The influence on the rigidity by the polymer plate is very high:

C1 = y of ceramics = 300.000 MPa
C2 = y of polymer =   2.700 MPa.

 - L1 and L2 is the overall mass of the system, whereby
    the mass of:

L1 = 3 Kgr/m^n ceramics and the mass of

L2 = 0,9 Kgr/m^n polymer.

Thus, the load on the polymer plate and the influence
thereupon is very high in order to have self-resonances
occur for certain frequencies. Thus, no resonances occur
due to harmonics or complex frequency signals.

The support or suspension of the vibration system has to
fulfill certain conditions.

1) The vibrations must be sufficiently attenuated in the
       suspension and not be refracted in the plate.
2) The suspension must be sufficiently rigid in order to
       keep the plate flat during bending.
3) The functional course of the difference of the distance
       between the circumference of the polymer membrane
       and the piezoceramic disk from the center of the
       polymer membrane must be positive or negative, and
       the course either has to be increasing or
       decreasing and not continuous, over an angle of at
       least 90°.
    Therefore, the covered distance between the edge of the
    membrane and the ceramic material is not constant, and
    no standing waves will occur which would show a
    concentrical nodal pattern, and therefore resonances
    are eliminated.

In figures 10 and 11, two embodiments of transducers 1
according to the invention are represented, which
transducers consist of a piezoceramic disk 2 and a membrane
3 made of synthetic material.

5   In these figures is:

      LM = length of the membrane of synthetic material
      R = radius of the ceramic disk
10   α = 90°
      SC = surface of the ceramic disk
      SM = surface of the membrane.

The functional course of a transducer 1 according to figure
15   10 is represented in figure 12, whereas that of the
transducer 1 according to figure 11 is represented in
figure 13, and whereby, if LM > R, then the function F is
(LM-R) over α = 90°.

20   The function is increasing and decreasing, positive and
discontinuous.

In the case of figure 11, LM > LC max.

25   In figures 14 to 19, several forms of embodiments of
transducers 1 according to the invention are represented,
whereby in figures 17, 18 and 19 the ceramic disk is
composed of several parts which are glued closely together
onto their carrier made of synthetic material and which are
30   connected to each other electrically.
As becomes clear from these figures, the ceramic disks may
have any shape.

As already discussed in the aforegoing, in figure 6 the harmonic contents of a transducer according to the aforementioned Belgian patent applications No. 09700309 and No. 09700934 is represented. The same signal of 1kHz is represented in figure 20 by a combination of a piezoceramic disk on a polymer plate, in which figure the pure reproduction of 1kHz is clearly visible, with its natural harmonics of 2kHz, 3kHz, 4kHz, 5kHz, 6kHz and 7kHz. Other peaks are not present or negligible.

A frequency characteristic measured with a pink noise generator of the same ceramics/polymer construction is represented in figure 21. A comparison with an electro-dynamic transducer with approximately the same surface area and the same harmonic reproduction of 1kHz is represented in figure 5.

The harmonic contents of 1kHz sinus represented by an electro-dynamic transducer and a combination of piezoceramics glued onto a polymer therefore is the same and equally pure.

In figure 22, a transducer 1 according to the invention is represented which consists of a ceramic disk 2 and a membrane 3 of synthetic material, for example, a polymer, whereby this transducer 1 is fixed in a suspension frame 5 by means of a flexible glue 6.

The frame 5 may be made in a variety of materials, such as, for example, synthetic material, polymer, wood, composite materials and such, on the condition that they form an attenuating material.

In order to attenuate the vibration energy which would be

created in the frame 5 due to transmission from the edge of the membrane 3 and, at the same time, to reduce the rigidity at the edge of the membrane, and thus allowing a more flexible movement due to the stretching and shrinking forces fo the ceramic disk 2, a number of grooves 7 are provided at the edge of the membrane 3 and over the entire circumference.

As a result, it is obtained:

- that vibrations in the suspension frame 5 are attenuated,
- that the amplitudinal deviation of the membrane 3 becomes larger,
- and that, due to the attenuation effect in the longitudinal direction, specific and spontaneous resonances are prevented or strongly reduced.

In figures 25 and 26, the electric schemes of the grooves 7 at the circumference of a polymer membrane 3, glued in to a frame 5, are represented.

Hereby are:

R = losses and attenuation in membrane 3
R = R1 + R2 + R3
C = rigidity of the membrane 3
C = C1 + C2 + C3
L = mass of the membrane 3
L = L1 + L2 + L3

Furthermore are:
$$R = \frac{1}{SP1} + \frac{1}{SP2} + \frac{1}{SP3}$$

$$C = yP \ (SP1 + SP2 + SP3)$$
$$L = gP \ (SP1 + SP2 + SP3)$$

herein are:

gP = specific weight of the polymer
yP = elasticity modules E of Young of the
     membrane material of the polymer
SA = section of the air
SP = section of the membrane material

A transducer 1 according to the invention can be provided
with a front plate 8, such as represented in figure 29,
which plate shows a number of openings 9.

By using such front plate 8 with a thickness T and with a
well-defined number of openings with diameter D, it is
possible to realize a reactive acoustic filter which will
refract a well-defined amount of energy.

Hereby, the surface of the openings 9 has a function as
capacity per length unit, whereas the wall thickness T has
a function as an inductance per length unit. See figures 29
and 30.

Hereby, it is valid that (see figure 31)

$$L = fwLdx$$
$$C = \frac{1}{fwLdx}$$
$$L \ tot = nL2\Pi r$$
$$C \ tot = \Pi r^2 n$$

whereby

r = radius of an opening 9
5   n = number of openings 9.

The suspension frame 5 must have a strongly attenuating function.

10   If we take, for example, the case of a frame 5 made of precious wood, such as beech, of 2 cm wide and 3 cm thick, and a membrane 3 of polypropylene with grooves 7 at the circumference of the membrane 3, whereby at the front, a filter is provided in the shape of a front plate 8 with a
15   thickness of 2 mm, in which a number of openings of 2 mm thickness are provided.

On the polypropylene membrane 3, two disks 2 are glued closely together and electrically connected to each other.
20

The construction of such reproduction element is represented in figure 32.

Hereby, the characteristics of the frequency analysis shows
25   an overall harmonic distortion of 2% and a reproduction pressure of average 74dB on a meter, see figure 20. The frequency reproduction is represented in figure 21.

In another construction, a round ceramic disk with a
30   diameter of 5 cm is glued onto a rectangular membrane 3 of synthetic material, for example, polypropylene, the extremities of which are folded downward and the extremities are folded back and thus mounted onto a carrier surface (see figure 33).

At the extremity of the flat part of the polypropylene membrane, a groove 7 has been provided up to 90% of the thickness of the membrane 3.

5

An alternative is to provide said groove up to 100% in order to form an air slot and to glue the rectangular portion created thereby to the circumference by means of an adhesive tape 10, such as represented in figures 35 and 36.

10

The frequency reproduction curve of this construction is represented in figure 37. Hereby, one will note that the refraction resonances from the edge suspension are almost entirely gone and that natural resonances of the membrane

15 3 and the ceramic 2 combination are not created, due to the functional difference of the circumference of the rectangle and the circle.

Still another example is represented in figure 38, whereby

20 the circumference of the membrane 3 is framed, by the intermediary of silicone glue 11, in a frame 5 with a U-shaped diameter and realized in synthetic material.

When the costs for industrial applications are important,

25 the simplicity of the construction is primary and the frequency reproduction may vary up to +/- 20dB, then a circular membrane 3 made of polymer onto which a circular ceramic disk 2 is glued and at the edge is glued into a circular frame 5 with silicones 11 or another flexible

30 glue, already is sufficient for realizing a very good music and speech reproduction. See the final results of the measurement of the frequency reproduction in figure 39, for a cylindrical and polymer membrane 3 with a diameter of 125 mm and a cylindrical ceramic disk 2 with a diameter of 100

mm.

The frequency distortion for this transducer is 3,5% for different frequencies, which is very acceptable for industrial purposes. See measurement figure 40.

In a certain embodiment, the transducer 1 according to the invention may be provided on an opened wall, in other words, a wall in which an opening is provided, whereby in that case the transducer is glued onto said wall by means of the membrane 3. Such application has a frequency reproduction of 50Hz to 20kHz, +/- 5Db, as represented in the measuring curve according to figure 40, whereby the membrane made of polypropylene has dimensions of 300 x 420 mm, the ceramic disk 2 has a diameter of 100 mm and the opening has a diameter of 260 mm.

Distortion measurements of this last-mentioned transducer, see figure 43, deliver a distortion of 1,5 % intermodular distortion. Such transducer may have, for example, a thickness of maximum 5 mm and comprises, for example, two electric connections with a diameter of 0,5 mm.

In figures 41 and 42, examples are represented of such application in an existing housing 12.

In a very particular application, whereby the housing of a device is made of a synthetic material, for example, polycarbonate, the piezoceramic disk 2 can be attached directly at said housing, whereby in this case one will think specifically of the housing of a cellular phone, telephone or similar, such as schematically represented in figure 43. In this case, the housing, so to speak, forms the membrane 3 in which preferably an opening 13 is

provided at the location of the ceramic disk 2.

In still another embodiment, see figure 44, the membrane 3 can be formed by a polymer film which either or not is
5 coated with a layer of metal 14 on which a connection 15 is provided and which is deformed by means of thermic vacuum technology, after which the disk of piezoceramics 2 can be glued onto the metal side of the polymer film. This latter may consist of a mixture of polymeres, elastomeres or
10 polyester.

The layer of metal 14 can, for example, be silver, gold, metal or another electric conductor which is brought into contact with one of the connections 15 of the transducer.
15 As the ceramics is glued onto this metal layer and makes a contact, thereby a wireless contact with the ceramic is realized, and the membrane can move without being hampered by a local load.

20 It is obvious that the present invention is in no way limited to the examples described in the aforegoing and represented in the accompanying drawings; on the contrary, such transducer according to the invention may be realized in a variety of forms and dimensions, without leaving the
25 scope of the invention.